

# DATA SHEET

## SONTRONICS STC-1S



**SONTRONICS**<sup>®</sup>  
 british design • world class

### Technical specifications

<b>Microphone type</b>	Stereo pair of small-diaphragm condensers
<b>Polar pattern</b>	Cardioid (optional OMNI and HYPER capsules are available)
<b>Frequency response</b>	25Hz to 20kHz
<b>Pad</b>	0dB, -10dB, -20dB
<b>Filter</b>	Linear, 75Hz, 150Hz
<b>Sensitivity (0dB = 1V/Pa @ 1kHz)</b>	12mV/Pa -36dB ±2dB
<b>Impedance</b>	≤200 Ohms
<b>Max. SPL (for 0.5% THD @ 1kHz)</b>	137dB
<b>Equivalent noise level</b>	16dB (A-weighted)
<b>Connector</b>	3-pin XLR
<b>Power</b>	Phantom power 48V required
<b>What's included</b>	STC-1S microphones, 2x mic clips, 2x foam windshields, stereo mounting bar, wooden box

### Other information

<b>Product weight</b>	214g x2
<b>Packaged weight</b>	2,121g
<b>Product dimensions</b>	162 x 24 x 24mm x2
<b>Packaged dimensions</b>	372 x 286 x 125mm
<b>Date introduced</b>	January 2005
<b>EAN-13 number</b>	5060173280031 (Black) 5060173280024 (Silver)

